

TRINKWASSER FLACHSCHLAUCH PUR LAY-FLAT HOSE FOR DRINKING WATER PUR



EIGENSCHAFTEN	abriebfeste Seele und Decke leicht
ARMATUREN	alle Standard Armaturen → Kapitel "Armaturen"
EINBAND	Schlauchschellen, Spannband
FEATURES	<i>abrasion-resistant tube and cover lightweight</i>
HOSE FITTINGS	<i>all standard fittings → chapter "Fittings"</i>
ASSEMBLING	<i>hose clamps, solid band</i>

Seele	<i>tube</i>	Polyurethan blau / <i>polyurethane blue</i>		
Einlage	<i>reinforcement</i>	Polyestergewebe / <i>polyester fabric</i>		
Decke	<i>cover</i>	Premium Ether Polyurethan blau / <i>premium ether polyurethane blue</i>		
Temperatur	<i>temperature</i>	-50°C / +50°C		
Biegeradius	<i>bending radius</i>	-		
Längen	<i>length</i>	200m und Abschnitte / <i>200m and cut-off length</i>		
				PUR - blau
DN Innen ø / <i>inner dia.</i> mm	Wandstärke <i>wall thickness</i> mm	Betriebsdruck* <i>working-pressure</i> bar	Gewicht <i>weight</i> ~ g/m	Art.-Nr.
25	1,8	25	160	751-492.025
50	2,5	25	470	751-492.050
75	2,5	20	700	751-492.075
100	2,5	18	1150	751-492.100
150	3,0	17	1650	751-492.150
200	3,2	13	2200	751-492.200
Einsatzbereich / <i>application</i>			Prüfungen Zulassungen / <i>tests approvals</i>	
Trinkwasser <i>drinking water</i>			KTW-A DVGW-W270 NSF 61 WRAS-BS6920	
* +20°C/H ₂ O Sicherheitsfaktor 2 / <i>safety factor 2</i>				